



Ball valve type 127 PVC-C 24V With manual emergency override With solvent cement sockets Inch ASTM Inclusive 2 threaded valve ends NPT

Model:

- Built on with electric actuator EA15
- Voltage 24V
- Factory set control range 90°<
- Heating element, position feedback (Open/Close)
- Integrated stainless steel mounting inserts

Option:

- Other valve and actuator configurations available
- Optional accessories: Fail-safe return unit

Size (inch)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (L/min)	EPDM Code	Weight (kg)	FKM Code	Weight (kg)
3/8	10	10	70	199 127 322	2.100	199 127 332	2.100
1/2	15	10	185	199 127 323	2.100	199 127 333	2.100
3/4	20	10	350	199 127 324	2.200	199 127 334	2.200
1	25	10	700	199 127 325	2.300	199 127 335	2.300
1 1/4	32	10	1000	199 127 326	2.600	199 127 336	2.600
1 1/2	40	10	1600	199 127 327	3.000	199 127 337	3.000
2	50	10	3100	199 127 328	3.800	199 127 338	3.800

Size (inch)	D (mm)	H (mm)	H1 (mm)	H2 (mm)	H3 (mm)	H5 (mm)	L (mm)	L1 (mm)	L2 (mm)	L4 (mm)	L5 (mm)	L6 (mm)	L7 (mm)	L8 (mm)	z (mm)
3/8	50	200	27	64	64	137	105	161	56	25	77	83	122	33	67
1/2	50	200	27	64	64	137	105	161	56	25	77	83	122	33	61
3/4	58	209	30	73	64	137	121	161	65	25	77	83	122	33	70
1	68	209	36	73	64	137	133	161	71	25	77	83	122	33	76
1 1/4	84	220	44	84	64	137	154	161	85	45	77	83	122	33	90
1 1/2	97	220	51	84	64	137	164	161	89	45	77	83	122	33	94
2	124	243	64	106	64	137	183	161	101	45	77	83	122	33	107

